



Product certificate K48872/06

Issued 2024-06-01

Replaces K48872/05

Page 1 of 2

Hose reels with semi rigid hose

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Uro-Flame B.V.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline

BRL-K 643/02: "Fixed firefighting systems. Hose systems: hose reels with semi-rigid hose", dated 01-02-2012,

which covers the requirements of

EN 671-1: 2012: "Fixed firefighting systems. Hose systems - Part 1: Hose reels with semi-rigid hose".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Uro-Flame B.V.
Noorderbaan 4
5388 RB NISTELRODE
Tel. +31 (0)412- 61 06 01
www.uro-flame.eu

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Hose reels with semi rigid hose

Technical specification

The products mentioned below belong to this certificate

manufacture: Uro-flame BV

type: Urohaspel

lengths: 20, 25 of 30 meter

nominal inner diameter hose: 13, 19 of 25 mm

disc diameter: 425, 525, 625 of 725 mm

installation depth: 127, 157 of 177 mm

working pressure: 15 bar

*Note: At the request of the customer, the above reel blade may be supplied in different colors or without coating. However, these reels do not fall under EN 671-1. According to EN 671-1, the color of the reel blade must be **RED**, deviation from the color does not affect the functionality.*

Application and use

Hose reels with semi-rigid hose are designed for fire fighting purposes and can be connected to drinking water installations with a working pressure up to 1000 kPa and a maximum water temperature of 30°C

Marking

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark:

- at the front on the disc,
- on the hose

Compulsory specifications:

- manufacturer's name or mark;
- the number of the European standard;
 - EN 671-1 on the hose reel;
 - EN 694 on the hose;
- year of manufacture;
- maximum working pressure;
- hose length and diameter;
- nozzle diameter (marked on the nozzle).

Method of marking:

- Non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Uro-Flame B.V.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.